

MZ-3333-01

Indoor/Outdoor – Vandal-Resistant IP Camera

IV&C

Industrial Video and Control

This vandal resistant, high-resolution color video camera with a vari-focal lens and auto-iris provides high quality video in difficult lighting conditions. When ambient light becomes too low, built-in IR illuminators switch on to provide near invisible lighting. The adjustable position mount and the 3.6 to 9 mm manual zoom lens can provide a horizontal field-of-view of up to 74 degrees.

The camera can accept one contact closure or TTL connect from auxiliary security or process-monitoring devices to initiate video recordings of intrusions or process upsets.

The enclosure is very rugged, vandal-resistant and weatherproof. It is suitable for indoor and outdoor use in prisons, college dorms, and other difficult applications. The camera is ready for mounting and requires only power and network connections.



Specifications

Imager	1/3" CCD sensor	Resolution	352x240 & 704x480
Shutter	1/60 to 1/100,000 sec.	Frame Rate	30 FPS (352x240) 15 FPS (704x480)
Exposure	Auto	Compression	M-JPEG; MPEG4
Min. Illumination	0 Lux w/ IR	Protocols	TCP/IP, HTTP, FTP, SMTP
White Balance	Auto	Weight	2 lbs
Iris	Auto	Power Input	12 VDC & 120 VAC
Gain	Auto	Operating Temperature	0° to 122° F
Focus	Manual	Dimensions	5.4" D x 4.5" H
View Angle	~30° - 74°		
Focal Length	3.6 - 9mm		
Ethernet	100Base-TX/10BaseT (RJ-45)		
I/O Terminals	One input, one output		