

PTZ-3130-LL

Outdoor - Pan Tilt Zoom - IP Camera

The PTZ-3130-LL is a high quality, high-resolution color video camera with outstanding low-light performance. It has an 18x motor-driven optical zoom and a 4x digital multiplier providing 72x total zoom. The pan, tilt and zoom functions can be controlled automatically and precisely from anywhere using the click-to-point, and preset view features in the IVC Relay Server. The PTZ camera is a high performance low-light camera that automatically switches to black and white and removes an IR cut filter to increase sensitivity in low light conditions.

The camera can accept one contact closure or TTL connect from an auxiliary security or process-monitoring device to initiate automatic views and video recordings of intrusions or process upsets.

The camera is housed in a weatherproof dome with an automatic heater and blower, and optional sun-shroud (SS-3130). The camera is ready for mounting and requires only a power and network connection. It can be factory configured for single or multimode fiber or wireless connections as well.



Specifications

Imager	1/4" Sony ExView CCD	Ethernet	100Base-TX/10BaseT (RJ-45)
Shutter	1 to 1/10,000 Seconds	Video	480 Lines (NTSC output on BNC)
Exposure	Auto	I/O Terminals	1 Input, 1 Output
Min. Illum.	0.7 Lux (Color) 0.005 Lux (B/W)	Resolution	704 x 480 and 352 x 240 pixels
White Balance	Auto	Compression	M-JPEG
Iris	Auto	Frame Rate	30 FPS (352x240) 10 FPS (704x480)
Focus	Auto and Manual	Protocols	TCP/IP, HTTP, FTP, SMTP
Zoom Ratio	18x Optical; 4x Digital 72x Total	Weight	14 lbs.
View Angle	2.8° - 48°	Power Req.	110V AC
Focal Length	4.1 – 73.8 mm	Power Cons.	50 W
F-number	1.4	Oper. Temp	-20 to 122° Fahrenheit
Pan Angle	360°	Dimensions	14" H x 11" D
Pan Speed	170° per Second	Mount	Wall Mount Standard
Tilt Angle	-90° to 0° (113° view range)		
Tilt Speed	90° per Second		